



Idropultrice professionale ad acqua fredda

Motore Loncin 4 tempi con avviamento a strappo autoavvolgente ed elettrico completo di batteria a secco. Pompa a pistoni in ceramica sistema biella/manovella e testata in ottone stampato. Manometro a bagno di glicerina. Carrello con maniglia, ruote pneumatiche e sostegni per accessori. Valvola by-pass automatica. Valvola di protezione termica. Dispositivo di regolazione pressione. Aspirazione detergente in bassa pressione con comando tramite lancia.

Accessori inclusi

Lancia completa con dispositivo alta e bassa pressione.
Tubo per alta pressione da mt.10.
Ugelli con attacco rapido da 0°, 15°, 25°, 40° e detergente.
Tubo alimentazione acqua da mt.3.

Cold water professional high pressure washer

4-stroke Loncin motor with self-rewinding and electric start complete with dry battery. Ceramic piston pump with rod/crank system and brass head. Glycerin pressure gauge. Trolley with handle, pneumatic wheels and accessory holders. By-pass automatic valve. Valve thermal protection. Pressure control device. Low pressure detergent suction through the lance.

Included accessories

Complete lance with high-low pressure device. Mt.10 high pressure hose.
Rapid coupling nozzles 0°, 15°, 25°, 40° and detergent. Mt.3 alimentation hose.



Tipo Type	Pressione Massima Max. Pressure		Portata Water Flow		N° giri/1'	Potenza Power	Peso Weight	Imballo Packaging		
	bar	psi	gph	l/h				L	P	H
LD 18/248	248	3600	270	1092	3400	13	85	880	700	880